











	Airbag		Stored gas inflator		Seat belt pretensioner		SRS control unit		Gas strut / Preloaded spring
	High strength zone		Battery low voltage		Fuel tank		Battery pack, high-voltage		High voltage component
	High voltage power cable		Cable cut						
ID No.		Version No.		Version date		Page			
4RUNNERHV55		01		12 / 2024		1 / 4			

## 1. Identification / Recognition



Lack of engine noise does not mean vehicle is off. Silent movement or instant restart capability exists until vehicle is fully shut down.

### Location of vehicle badges




### Energy source: Nickel metal hydride battery




## 2. Immobilisation / Stabilisation / Lifting

### Completely immobilize the vehicle




1) Chock the wheels and engage the parking brake.



2) Move the shift lever to the park (P) position.

### Stabilisation-lifting point

Place cribbing such as wooden blocks at the four points under the front and rear pillars.



Extra Reinforced Lifting Points



Standard Jack Locations



Vehicle Center of Gravity



Do not place cribbing such as wooden blocks or rescue air lifting bags under the exhaust system, fuel system or high voltage power cables. Doing so may result in fuel leaks, fire, or electric shock.

ID No.	Version No.	Version date	Page
4RUNNERHV55	01	12 / 2024	2 / 4


3. Disable direct hazards / Safety regulations

■ If any of the following systems are required to be operated, operate them BEFORE disconnecting the battery.


- Power door lock
- Power window
- Back door opener
- Power Back door
- Moon roof
- Power seat
- Power tilt and telescopic steering
- Electric parking brake

When the 12 V battery is disconnected, electrical components cannot be operated.

■ Perform procedure Main or Alternative to completely shut off the vehicle.  
<Main Procedure>




<Alternative Procedure>




In the event of an accident in which the airbags are deployed, the high-voltage system will be automatically deactivated.

■ Access to 12 V Battery



4. Access to the occupants


■ Window Glass




A	Laminated	B	Tempered
---	-----------	---	----------

ID No.	Version No.	Version date	Page
4RUNNERHV55	01	12 / 2024	3 / 4


5. Stored energy / Liquids / Gases / Solids




High Voltage Ni-MH Battery









12 V Battery



Gasoline Tank: 72.0 L









- Always wear appropriate personal protective equipment (PPE) when dealing with any of these items.
- Never breach or remove the battery assembly cover under any circumstances, including fire. Doing so may result in serious injury or death from severe burns or electric shock.






6. In case of fire




USE COPIOUS AMOUNTS OF WATER


If it is difficult to apply copious amounts of water to the high voltage battery, it is recommended to allow the high voltage battery to burn itself out.








RE-IGNITION POSSIBLE !



Gas strut / Preloaded spring  
As it is possible for a gas strut / preloaded spring to become a projectile, refer to the component layout drawing




7. In case of submersion




Do not touch any of the high-voltage components or cables, including the service plug, while the vehicle is submerged. Doing so may result in electric shock.

Work on the vehicle only after the vehicle has been pulled out of the water.

8. Towing / Transportation / Storage





RE-IGNITION POSSIBLE !

Store the vehicle at a safe distance (15 m (49.2 ft) or more) from other vehicles.

9. Important additional information

For more details, please refer to "Emergency Response Guide."  
<https://www.techinfo.toyota.com>

	ID No.	Version No.	Version date	Page
	4RUNNERHV55	01	12 / 2024	4 / 4